1 Publication number:

0 314 642 A1

12

EUROPEAN PATENT APPLICATION

21 Application number: 88830442.5

2 Date of filing: 25.10.88

(s) Int. Cl.4: B 60 R 1/00

B 60 R 11/02

39 Priority: 26.10.87 IT 6789287

43 Date of publication of application: 03.05.89 Bulletin 89/18

Designated Contracting States:
 AT CH DE ES FR GB LI

(T) Applicant: SAME S.p.A.
Viale F. Cassani, 14
I-24047 Treviglio Bergamo (IT)

(7) Inventor: Bergese, Claudio c/o Same S.p.A. Viale F. Cassani, 14 I-24047 Treviglio (Bergamo) (IT)


> Vicentini, Vittorio c/o Same S.p.A. Viale F. Cassani, 14 I-24047 Treviglio (Bergamo) (IT)

Hampel, Gerard c/o Same S.p.A. Viale F. Cassani, 14 I-24047 Treviglio (Bergamo) (IT)

Representative: Buzzi, Franco et al c/o Jacobacci-Casetta & Perani S.p.A. Via Alfieri, 17 I-10121 Torino (IT)

(54) Comprehensive monitoring system for the drivers' cabs of tractors.

(g) A comprehensive monitoring system for the drivers' cabs of tractors, comprising a television display (1) with a loud-speaker (2), a tuning-detection-colour matrix-audio-video control unit (6), a television camers (4), an interface and conditioning unit (5) arranged to receive input signals from sensors installed on the tractor, a mixing and processing unit (3) connected between the television display and the interface and conditioning unit and connected to the control unit and to the television camera, and a control unit and to the television camera, and a control unit and to the processing unit.



EP 0 314 642 A1

Description

Comprehensive monitoring system for the drivers' cabs of tractors.

10

15

25

30

35

40

45

50

The subject of the present invention is a comprehensive monitoring system for the drivers' cabs of tractors.

1

The system is characterised in that it comprises: - a display, normally of television type, provided with a loudspeaker,

- a tuning-detection colour matrix-audio-video control unit controllable by serial means and also provided with tuning-detection for radio-television transmitters,
- one or more television cameras, possibly orientable, adapted for installation on the tractor in a rearward-looking position and possibly provided with remote controls (focusing, zoom, etc.).
- an interface and conditioning unit arranged to receive input signals from sensors and detectors installed on the tractor.
- a mixing and processing unit connected between the television display and the interface and conditioning unit and connected to the control unit and the television camera, and
- a control keyboard connected to the processing unit.

Preferably, the system also includes an audiovideo recorder (video disc, video cassette, etc.) connected to the processing unit.

The comprehensive monitoring system according to the invention makes available to the operator of the tractor, in a direct and convenient manner, a plurality of functions which may be summarised as follows:

- instrumentation
- . Interactive electronic dashboard
- . check panel
- . performance monitor
- . diagnostics
- exchange of controls and data between operators and electronically controlled equipment;
- rearward vision
- . detailed/panoramic vision of the working area
- . detailed/panoramic vision of the positioning of equipment;
- entertainment and instruction
- . reception from radio-television transmitters
- . video-cassette recording (also with operating instructions).

The invention will now be described in more detail with reference to the appended drawing, provided purely by way of non-limiting example, which shows in diagrammatic form the layout of the comprehensive monitoring system for drivers' cabs of tractors according to the invention.

With reference to the drawing, the system according to the invention includes a black-and-white or colour TRC-type monitor 1 with an associated loudspeaker 2, both installed in the driver's cab of a tractor in a position where they can easily be seen by the driver. The monitor 1 is conveniently provided with a 6-10" diagonal medium-resolution screen and is suitable both for the reproduction of television pictures and for the reproduction of graphic sym-

bols.

The monitor 1 is connected to an electronic processing unit 3 arranged to receive, in the manner explained below, signals to be processed according to one or more predetermined programs, and to display the results in the form of images and audio signals by means of the monitor 1 and the loudspeaker 2. In particular, the processor 3 is able to fulfil the functions of processing and mixing of signals, generation of symbols and alpha-numeric messages, organisation of priorities, supervision and diagnostics.

The signals sent to the processor 3 come from a television camera 4, from an interface and conditioning unit 5, from a control unit 6, and from a control keyboard 7.

The television camera 4, which may be black-and-white or colour, is of the remotely orientable type and possibly provided with automatic or remote-controlled focusing or zoom. It is arranged for installation in the rear region of the vehicle for detailed or panoramic cover of the working area and/or of the positioning of the equipment attached to the rear of the tractor.

The interface and conditioning unit 5 is provided with a series of inputs 5a connected to sensors, detectors and any other processing unit on the tractor, and is arranged normally to acquire the following classes of input signals:

- on-off signals, earthed or at +12V
- 0-5/0-12V earthed analogue signals;
- differential analogue signals, 0-1 V/O-12V;
- preformed pulse signals-0-10 KHz TTL levels from phonic wheels, variable-reluctance sensors;
- line or lines for connection to transported equipment provided with electronics.

The control unit 6 is constituted by a tuning-detection-colour matrix-audio-video unit controllable by serial means (remote control channel) through the processor 3. It is also provided with electronics for amplification, selection, and detection of audio and video signals in black-and-white or colour, broadcast by electromagnetic wave transmitters, for example, AM/FM radio stations and/or television transmitters.

The control keyboard 7 may be of conventional push-button type or of the "Touch screen" type, or even a cursor control of the "Track ball" or "Joystick" type, etc.

The processing unit 3 is also provided with a socket 8 for possible connection of a video cassette recorder.

By virtue of the above-described conformation, the monitoring system according to the invention is able to fulfil the following main functions:

- instrumentation
- . interactive electronic dashboard
- . check panel
 - . performance monitor
 - . diagnostics
 - . exchange of control and data between the operator

2

60

IDOCID: <EP____0314642A1_[_>

5

10

15

20

25

30

35

40

45

50

55

60

and electronically controlled equipment;


- rearward vision
- . detailed/panoramic vision of the working area . detailed/panoramic vision of the positioning of equipment;
- entertainment and instruction
- . reception of television transmissions
- . video cassette recording, also with operating instructions.
- It is possible to present several classes of information simultaneously, for example, superimposed on part of the screen (windowing), etc.. In the case of conflicting demands, the central processor organises the display priority. This occurs according to prearranged preceding levels so as to ensure signalling appropriate to the importance of the event.

Claims

- 1. A comprehensive monitoring system for drivers' cabs and for tractors, characterised in that it comprises:
- an image display (1) provided with a loudspeaker (2),
- a tuning-detection-colour matrix-audio-video control unit controllable by serial means and

also provided with tuning-detection control for radio-television transmitters,

- at least one television camera (4), possibly orientable, adapted for installation on the tractor in a rearward-looking position and possibly provided with remote controls,
- an interface and conditioning unit (5) arranged to receive input signals from sensors and detectors installed on the tractor, the interface unit being further provided with input/output communications with any equipment attached to the tractor,
- a signal processing and mixing unit (3) connected between the television display (1) and the interface and conditioning unit (5) and connected to the control unit (6) and the television camera (4),
- a control keyboard (7) operatively connected to the processing and mixing unit (3).
- 2. A system according to Claim 1, characterised in that it also includes an audio-video recorder (8) connected to the processing and mixing unit (3).
- 3. A system according to Claim 1 or Claim 2, characterised in that the processing unit (3) is arranged to present information on the display (1), according to a hierarchical system of prearranged precedence levels.



EUROPEAN SEARCH REPORT

Application Number

EP 88 83 0442

C-4	Citation of document with	indication, where appropriate,	Relevant	CLASSIFICATION OF THE
Category	of relevant p		to claim	APPLICATION (Int. Cl.4)
Υ	DE-A-1 555 360 (FE * Claims 1-4; figur		1	B 60 R 1/00 B 60 R 11/02
A			2,4	
Υ	WO-A-8 404 499 (EF * Pages 1-2; figure	RNST)	1	
A		: -	2,4	
A	DE-A-2 223 816 (NI * Page 3, line 7 - figure 1 *	IPPON DENSO K.K.) page 5, line 13;	1-3	
A	GB-A-2 144 682 (JA * Page 1, lines 5-2	ACOBS) 23; figure 2 *	1-3	:
A	FR-A-2 465 612 (SA * Page 2, lines 20-		ī	
		•		TECHNICAL FIELDS SEARCHED (Int. Cl.4)
				B 60 R
•				H 04 N
			ŀ	
				ķ.
·····	The present search report has	been drawn up for all claims	-	
Place of search THE HAGUE		Date of completion of the search 25-01-1989	MAU	Examiner USSER, T.
Y: par do:	CATEGORY OF CITED DOCUMI rticularly relevant if taken alone rticularly relevant if combined with a cument of the same category	after the film nother D : document cit L : document cit	ed in the applications of the second	on S
A : technological background O : non-written disclosure P : intermediate document			e same patent fam	nily, corresponding

INSDOCID: <EP